

EP-517T 16 Port 10M Ethernet Desktop Hub with 1 BNC Port



Features

- IEEE802.3 10 Base-T compliant
- 1 RJ-45 uplink port shared with Port #17 as the cascading port
- Port auto-partition and reconnection to facilitate faulty segment isolation
- Data collision and jabber handling functions
- · Compact Design for Desktop or Wall-mount

Specifications

Model	EP-517T
Description	16 Port 10M Ethernet Mini Hub with 1 BNC Port
Standard	IEEE 802.3 10Base-T, 10Base 2
Access Method	CSMA/CD
No. of Port	16*RJ-45 and 1*BNC
Uplink Port	1 RJ-45 Port as the cascading port
Date Rate	10Mbps
LED Indicator	Link/Act, Power, Collision
Dimension (L*W*H)mm	165 X 88 X 23 mm
Net Weight	190 g
Temperature	Operating: $0^{0} \sim 55^{0}$; Storage: $0^{0} \sim 65^{0}$
Humidity	Operating: 10% ~ 90% ; Storage: 5% ~ 95%
Conformance	FCC, CE

Ordering Information

Model	Description
EP-517T	16 Port 10M Ethernet Mini Hub with 1 BNC Port

SURECOM Technology Corp.

6th Fl., 15, Sec. 2, Datung Road, Shijr city, Taipei 221, Taiwan Tel: 886-2-8692-6200 Fax: 886-2-8692-6132 e-mail: <u>sales@surecom.com.tw</u> website: <u>www.surecom.com.tw</u> / <u>www.surecom-net.com</u>